

Cerami-Bond™

Premium Epoxy Mortar Tile Adhesive



Features & Benefits

Wear-Con **Cerami-Bond™** Premium Epoxy Mortar Tile Adhesive is an industrial grade 100% solids epoxy paste for use in bonding ceramic tiles. **Cerami-Bond™** cures at room temperature to a tough solid. **Cerami-Bond™** adheres to almost any clean surface, including metal, glass, ceramics and many other areas.

Installation

Wear-Con **Cerami-Bond™** is easy to mix and install. Simply mix one part Resin - Part A with one part Hardener - Part B and trowel on both surfaces. **Cerami-Bond™** is workable for up to 45 minutes at 70°F.

Technical Specifications

Wear-Con **Cerami-Bond™** adheres to contaminant free clean surfaces in working temperatures from 60°F to 110°F continuously. Cured **Cerami-Bond™** has a compressive strength of 15,150 psi, a tensile strength of 5,000 psi, maximum operating lap shear of 2,350 psi and a maximum operating temperature of 210°F.

Sizes

Wear-Con **Cerami-Bond™** is only available in 2 gallon kit quantities, (1 gal. resin and 1 gal. hardener).

(See reverse for **Cerami-Bond™** applications.)

2845 E. Heartland Drive
Liberty, MO 64068

888-4WEARCON (888-493-2726)
816-587-1923 • Fax 816-587-2055
info@wearcon.com
www.wearcon.com



Cerami-Bond™

Premium Epoxy Mortar Tile Adhesive



WC90™ Plain Ceramic Tile installed with **Cerami-Bond™**.



WC90™ Plain Ceramic HexTile & Weldable Ceramic Tile installed with **Cerami-Bond™**.

(See reverse for **Cerami-Bond™** information.)



888-4WEARCON (888-493-2726)
816-587-1923 • Fax 816-587-2055
info@wearcon.com
www.wearcon.com



Applications:

- Plain Ceramic Tile
- Weldable Ceramic Tile
- Hex Tile

2845 E. Heartland Drive
Liberty, MO 64068

CER-BND

10-17