

Cerami-Bond™

Premium Epoxy Mortar Tile Adhesive



Features & Benefits

Wear-Con **Cerami-Bond™** Premium Epoxy Mortar Tile Adhesive is an industrial grade 100% solids two-part epoxy paste for use in bonding ceramic tiles. Cerami-Bond™ is especially suited for use in wear tile applications requiring high bond strength, physical properties and good chemical resistance. **Wear-Con Cerami-Bond™** is resistant to caustic solutions, most diluted acids, hypochlorite bleaches, and other harsh chemicals. **Cerami-Bond™** cures at room temperature to a tough solid. **Cerami-Bond™** adheres to almost any clean surface.

Installation

Wear-Con **Cerami-Bond™** is easy to mix and install. Simply mix one part Resin - Part A with one part Hardener - Part B and trowel on both surfaces. **Cerami-Bond™** offers excellent troweling and handling characteristics with sufficient body and thixotropy to butter brick in place and secure them from slipping or sliding while the mortar cures. **Cerami-Bond™** cures rapidly and provides an excellent bond to brick, tile, and steel. This unique formulation produces excellent results while installing brick in horizontal, vertical, and even overhead areas. **Cerami-Bond™** is workable for up to 45 minutes at 70°F.

Technical Specifications

Wear-Con **Cerami-Bond™** adheres to contaminant free clean surfaces in working temperatures from 60°F to 110°F continuously. Cured **Cerami-Bond™** has a compressive strength of 11,500 psi, a tensile strength of 3600 - 4100 psi and a maximum operating temperature of 275°F and One two-gallon unit of **Cerami-Bond™** covers approximately 14² ft of tile lining when used as a setting bed for tile with a nominal 1/16" joint thickness between the tile.

Sizes

Wear-Con **Cerami-Bond™** is available in 2 gal. kit quantities, (1 gal. resin and 1 gal. hardener).

(See reverse for **Cerami-Bond™** applications.)

2845 E. Heartland Drive
Liberty, MO 64068

888-4WEARCON (888-493-2726)
816-587-1923 • Fax 816-587-2055
info@wearcon.com
www.wearcon.com



Cerami-Bond™

Premium Epoxy Mortar Tile Adhesive



WC90™ Plain Ceramic Tile installed with Cerami-Bond™.



WC90™ Plain Ceramic HexTile & Weldable Ceramic Tile installed with Cerami-Bond™.

(See reverse for Cerami-Bond™ information.)



888-4WEARCON (888-493-2726)
816-587-1923 • Fax 816-587-2055
info@wearcon.com
www.wearcon.com

Applications:

- Plain Ceramic Tile
- Weldable Ceramic Tile
- Hex Tile

2845 E. Heartland Drive
Liberty, MO 64068