

Triple-Bead⁹⁰™

Ceramic Wear-Compound



Triple-Bead⁹⁰™

Bucket Kit Includes:

- 1 Gallon Resin Part A
- 1 Gallon Hardener Part B
- 1 Pair Latex Gloves
- 1 Trowel

Part #12490



Triple-Bead⁹⁰™

Patch Kit Includes:

- 1 lb Resin Part A
- 1 lb Hardener Part B
- 1 Pair Latex Gloves
- 1 Mini-Trowel

Part #12491



Triple-Bead⁹⁰™

Patch Kit XM Includes:

- 1 lb Resin Part A
- 1 lb Hardener Part B
- 1 Pair Latex Gloves
- 1 Mini-Trowel
- 6 - 3"x6" Expanded Metal Mesh Pieces

Part #12492



Features & Benefits

Simple to mix. Simple to use. Simply the best! Wear-Con **Triple-Bead⁹⁰™** Ceramic Wear Compound's ceramic beads are the perfect size for any job: small enough for pump housings, yet large enough for chutes. Providing excellent resistance to sliding and fine particle abrasion, **Triple-Bead⁹⁰™** is an essential part of any quick repair job.

Installation

Wear-Con **Triple-Bead⁹⁰™** is easy to mix and install. Simply mix one part **Triple-Bead⁹⁰™** Resin - Part A with one part **Triple-Bead⁹⁰™** Hardener - Part B and trowel on. **Triple-Bead⁹⁰™** is workable for up to 45 minutes, and is water soluble until curing is complete.

Technical Specifications

Wear-Con **Triple-Bead⁹⁰™** can be used in applications with temperatures up to 250°F (for higher temperatures see reverse). Due to its paste consistency sagging is not an issue, therefore **Triple-Bead⁹⁰™** conforms to irregular and overhead surfaces. **Triple-Bead⁹⁰™** cures chemically, resulting in minimal shrinkage. Moh's Hardness Scale of 9 for beads, Compressive Strength is 10,000 psi, Tensile Strength of 3600-4100 psi, Flexural Strength N/A, Shear Strength N/A, Absorbion Rate is 0.24%.

Sizes

Wear-Con **Triple-Bead⁹⁰™** is available in both 28.6 lb Bucket Kits and convenient 2 lb Patch Kits containing everything you need to get the job done.

Standard Coverage		
Kit	Thickness	Coverage
28.6 lb Bucket Kit	1/4"	11.83 sq. ft.
2 lb Patch Kits	1/4"	0.84 sq. ft.

(See reverse for **Triple-Bead⁹⁰™** High-Temp)

2845 E. Heartland Drive
Liberty, MO 64068

888-4WEARCON (888-493-2726)
816-587-1923 • Fax 816-587-2055
info@wearcon.com
www.wearcon.com

