

Triple-Bead *™* High-Temp Bucket Kit Includes:

- 1 Gallon Resin Part A
- 0.25 Gallon Hardener Part B
- 1 Pair Latex Gloves
- 1 Trowel

Part #12590



Triple-Bead MHigh-Temp Patch Kit Includes:

- 1 lb Resin Part A
- 0.25 lb Hardener Part B
- 1 Pair Latex Gloves
- 1 Mini-Trowel

Part #12591



Triple-Bead *M* High-Temp Patch Kit XM Includes:

- 1 lb Resin Part A
- .25 lb Hardener Part B
- 1 Pair Latex Gloves
- 1 Mini-Trowel
- 6 3"x6" Expanded

 Metal Mesh Pieces

 Part #12592



Features & Benefits

Simple to mix. Simple to use. Simply the best! Wear-Con Triple-Bead[™] High-Temp Ceramic Wear Compound's ceramic beads are the perfect size for any job: small enough for pump housings, yet large enough for chutes. Providing excellent resistance to sliding and fine particle abrasion, Triple-Bead[™] High-Temp is an essential part of any high-temp quick repair job.

Installation

Wear-Con Triple-Bead[™] High-Temp is easy to mix and install. Simply mix four parts Triple-Bead[™] High-Temp Resin - Part A with one part Triple-Bead[™] High-Temp Hardener - Part B and trowel on. Triple-Bead[™] is workable for up to 45 minutes, and is water soluble until curing is complete.

Technical Specifications

Wear-Con Triple-Bead[™] High-Temp can be used in applications with temperatures up to 450°F continuously. Due to its paste consistency sagging is not an issue, therefore Triple-Bead[™] High-Temp conforms to irregular and overhead surfaces. Triple-Bead[™] cures chemically, resulting in minimal shrinkage. Moh's Hardness Scale of 9 for beads, Compressive Strength is 10,000 psi, Tensile Strength of 3600-4100 psi, Flexural Strength N/A, Shear Strength N/A, Absorbsion Rate is 0.24%.

Sizes

Wear-Con **Triple-Bead**^{∞™} High-Temp is available in both 28.6 lb Bucket Kits and convenient 2 lb Patch Kits containing everything you need to get the job done.

Standard Coverage		
Kit	Thickness	Coverage
28.6 lb Bucket Kit	1/4"	11.83 sq. ft.
2 lb Patch Kits	1/4"	0.84 sq. ft.

(See reverse for Triple-Bead%)

2845 E. Heartland Drive Liberty, MO 64068 OR-WC 11-17 888-4WEARCON (888-493-2726) 816-587-1923 • Fax 816-587-2055 info@wearcon.com www.wearcon.com

